

06-30-00

A

DOCKET: CU-2258 RJS

Assistant Commissioner for Patents
Box PATENT APPLICATION
Washington, D.C. 20231

06/29/00
JCS60 U.S. PRO

L 467 816595

"EXPRESS MAIL" mailing label number
Date of Deposit June 29, 2000
I hereby certify that this paper or fee is being
deposited with The United States Postal Service
"Express Mail Post Office To Addressee" Service
under 37 CFR 1.10 on the date indicated above and
is addressed to: Commissioner of Patents and
Trademarks, Washington, D.C. 20231
Seung Ho Hong et al
(Name of applicant, assignee, or Registered Rep.)
Debra M. Szumowski
(Name of person mailing paper or fee)
(Signature of person mailing paper or fee)

Sir:

Transmitted herewith for filing is the patent
application of:

Inventor: Seung Ho HONG et al

Title: REFLECTIVE TYPE-FRinge FIELD SWITCHING MODE LCD

Enclosed are the following papers and documents required for filing date
under 37 CFR 1.53(b):

- 15 Pages of specification
- 3 Pages of claim(s)
- 1 Pages of abstract
- 11 Sheets of drawing
- X Combined Declaration and Power of Attorney
- X An assignment of the invention to: Hyundai Electronics Industries Co., Ltd.
- X A certified copy of a Korean (1999-25214) application
- Verified Statement to establish small entity status under 37 CFR 1.9 and 37 CFR 1.27
- X Assignment Recordation Cover Sheet with accompanying fee
- Other:

The filing fee has been calculated as shown below:

	(Col. 1)	(Col. 2)
•FOR:	NO. FILED	NO. EXTRA
BASIC FEE		
TOTAL CLAIMS	10 -20=	* 0
INDEP CLAIMS	2 -3=	* 0
☐ MULTIPLE DEPENDENT CLAIM PRESENTED		

*If the difference in Col. 1 is less than zero, enter "0"
in Col. 2

SMALL ENTITY		OR	OTHER THAN A SMALL ENTITY	
RATE	FEE		RATE	FEE
	\$345.	OR		\$690.
x 9.	\$	OR	x 18.	\$ -
x 39.	\$	OR	x 78.	\$ -
+ 130.	\$	OR	+ 260.	\$ -
TOTAL	\$	OR TOTAL	\$ 690.	

☒ A check in the amount of \$ 690.00 to cover the filing fee is enclosed.

☒ The Commissioner is hereby authorized to charge payment of any additional
filing fees associated with this communication, or credit any overpayment
to our Deposit Account No. 12-0400. A duplicate copy of this sheet is
attached.

June 29, 2000

Date

Respectfully submitted,

Richard J. Streit
Attorney for Applicant(s)

RICHARD J. STREIT
LADAS & PARRY
224 SOUTH MICHIGAN AVENUE
CHICAGO, ILLINOIS 60604
Reg. No. 25765 (312) 427-1300

REFLECTIVE TYPE-FRINGE FIELD SWITCHING MODE LCD**FIELD OF THE INVENTION**

The present invention relates to a reflective type
5 liquid crystal display, more particularly to a reflective-
type fringe field switching mode LCD(hereinafter,
reflective FFS-LCD) capable of improving a reflection rate
thereof.

BACKGROUND OF THE INVENTION

A twisted nematic(TN) mode LCD having nematic liquid
crystal compositions of positive dielectric anisotropy has
been used for the conventional reflective type LCD. This
reflective type TN-LCD has a low power consumption property
15 and is used for relatively small size LCDs of an electronic
clock, a digital clock and so on. However, the reflective
TN-LCD has chronic problems of a poor viewing angle and a
low contrast ratio.

Consequently, a reflective FFS-LCD device is now in the
20 process of research and development to ensure a good
viewing angle property, a high reflective rate and an
aperture ratio. The composition of this conventional
reflective FFS-LCD device is approximately illustrated in
FIGs. 1 and 2.

Referring to FIGs. 1 and 2, a lower substrate 10 is
opposed to an upper substrate 15 at a selected distance. A
liquid crystal layer 17 having a plurality of liquid
crystal molecules is interposed between the lower substrate
10 and the upper substrate 15. A counter electrode 11a and
30 a pixel electrode 11b forming a fringe field to operate the
liquid crystal molecules, are disposed on the inside
surface of the lower substrate 10. A color filter(not
shown) is disposed on the inside surface of the upper
substrate 15. A first homogeneous alignment layer 12 is
35 interposed between the lower substrate 10 including the
counter electrode 11a and the pixel electrode 11b, and the

liquid crystal layer 17. A second homogeneous alignment layer 16 is interposed between the upper substrate 15 including the color filter and the liquid crystal layer 17. At this time, the first and the second homogeneous alignment layers 12,16 have rubbing axes R1,R2 respectively, and the rubbing axis R1 of the first homogeneous alignment layer 12 and the rubbing axis R2 of the second homogeneous alignment layer 16 form 180° , i.e. anti-parallel to each other. In addition, the rubbing axis R1 forms a selected angle with a line f which on the substrate surface, projects the fringe field that is formed between the counter electrode 11a and the pixel electrode 11b. A polarizer 8 is attached on the outside surface of the upper substrate 5 so that polarizing axis 8a thereof is equal to the rubbing axis R1 of the first homogeneous alignment layer 12. A $\lambda/4$ plate 19 polarizing an incident light or a reflected light by $\lambda/4$ is disposed on the outside surface of the lower substrate 10. On the outside of the $\lambda/4$ plate 19, a reflective plate 20 reflecting the light which passes through the $\lambda/4$ plate 19, is disposed. At this time, the $\lambda/4$ plate 19 is disposed so that a fast(or slow) axis thereof is at an angle of 45° with the first rubbing axis(R1).

Such conventional reflective-type FFS-LCD operates as following.

First, referring to FIG. 1, when voltage difference does not occur between the counter electrode 11a and the pixel electrode 11b, the liquid crystal molecules(not shown) are arranged so that the rubbing axes R1,R2 and the long axes thereof are parallel. Consequently, a natural light 22a becomes an incident light 22b proceeding to the same direction as a polarization axis 18a by passing through a polarizer 18. Thereafter, the direction of the incident light 22b is not changed while passing through the liquid crystal layer 17 which the rubbing axes R1,R2 and the long axes of the liquid crystal molecules are arranged

side by side thereon. The incident light 22b which has passed through the liquid crystal layer 17, is at an angle of 45° with the fast(or slow) axis of the $\lambda/4$ plate 19, thereby becoming a right-circularly polarized light 22c passing through the $\lambda/4$ plate 19. The right-circularly polarized light 22c is reflected by a reflective plate 20, thereby becoming a right-circularly polarized reflected light 23a.

The reflected light 23a becomes the reflected light 23a proceeding to a crossing direction with the axis of the polarized light 18a, passing through the $\lambda/4$ plate 19 having the fast(or slow) axis at an angle of 45° with the proceeding direction thereof. The proceeding direction of the reflected light 23b which has passed through the $\lambda/4$ plate 19, is orthogonal to the long axis of the liquid crystal layer 17, thereby passing through the liquid crystal layer 17 without being changed. The reflected light 22b which has passed the liquid crystal layer 17, is orthogonal to the polarizing axis 18a, thereby not passing through the polarizer 18. Accordingly, a screen becomes dark.

Next, like FIG. 2, when a fringe field F is formed between the counter electrode 11a and the pixel electrode 11b, the liquid crystal molecules(not shown) are twisted into the fringe field form. Consequently, the optical axes of the liquid crystal molecules(not shown) are at a selected angle with the polarizing axis 18a. A natural light 25a passes through the polarizer 18, thereby becoming an incident light 25b proceeding to the same direction as the polarizing axis 18a. Thereafter, the incident light 25b is at an angle of 45° with a long axis of a liquid crystal molecule which is arranged in a fringe field F form. Therefore, an incident light 25c which has passed through the liquid crystal layer 17, becomes the incident light 25c which is at an angle of 45° with the polarizing axis 18a. Here, the incident light 25c which has passed through the

liquid crystal layer 17 coincides with the fast(or slow) axis 19a of the $\lambda/4$ plate 19, thereby passing through the $\lambda/4$ plate 19 without change in the proceeding direction thereof. The incident light 25c which has passed through the $\lambda/4$ plate 19, is reflected by the reflective plate 20, thereby becoming a reflected light 26a.

The proceeding direction of the reflected light 26a coincides with the fast(or slow) axis of the $\lambda/4$ plate 19, thereby passing through the $\lambda/4$ plate 19 without changing the proceeding direction thereof. The proceeding direction of the reflected light 26a which has passed through the $\lambda/4$ plate 19, is at an angle of 45° with the long axis of the liquid crystal molecule on the liquid crystal layer 17 and therefore the proceeding direction of a reflected light which has passed through the liquid crystal layer 17, coincides with the polarizing axis 18a. Therefore, a screen is in a white state.

Conventional reflective type liquid crystal display device has not required a backlight as light source and optical component such as the $\lambda/4$ plate 19 has been added to the outside of a substrate thereof to improve a contrast.

However, the manufacturing cost is increased as the optical component such as the $\lambda/4$ plate is added. Moreover, the $\lambda/4$ plate absorbs some of an incident light or a reflected light, thereby deteriorating transmissivity of the LCD, i.e. the reflectance.

SUMMARY OF THE INVENTION

Accordingly, an object of this invention is to provide a reflective type liquid crystal display device having a good contrast ratio and a good reflectance without an additional optical component.

To accomplish the aforementioned object of this invention, the present invention according to a first embodiment provides a reflective type FFS-LCD including: a

liquid crystal layer having a plurality of the liquid crystal molecules; a first substrate disposed on one side of the liquid crystal layer and in which a counter electrode and a pixel electrode, both for generating a fringe field to drive the liquid crystal molecules are formed; a second substrate disposed on the other side of the liquid crystal layer; a first homogeneous alignment layer interposed between the liquid crystal layer and the first substrate and having a rubbing axis in a selected direction; a second homogeneous alignment layer interposed between the liquid crystal layer and the second substrate, and having a rubbing axis in a selected direction; a polarizer disposed on an out side of one of the first substrate and the second substrate, and having a selected polarizing axis; and a reflective plate disposed on an out side of the other of the first substrate and the second substrate, wherein retardation of the liquid crystal layer is $(2n+1)\lambda/4$ (here, λ is wave of light and n is a positive number).

The present invention according to another embodiment, also provides a reflective type FFS-LCD including a liquid crystal layer having a plurality of liquid crystal molecules; a first substrate disposed on one side of the liquid crystal layer and on which a counter electrode and a pixel electrode, both for generating a fringe field to drive the liquid crystal molecules are formed; a second substrate disposed on the other side of the liquid crystal layer; a first homogeneous alignment layer interposed between the liquid crystal layer and the first substrate and having a rubbing axis in a selected direction; a second homogeneous alignment layer interposed between the liquid crystal layer and the second substrate and having a rubbing axis in a selected direction anti-parallel to the rubbing axis of the first homogeneous alignment layer; a polarizer disposed on an out side of one of the first substrate and

the second substrate, and having a selected polarizing axis; and a reflective plate disposed on an out side of the other substrate of the first substrate and the second substrate, wherein the rubbing axes of the first and the second alignment layers are at an angle of 10 to 85° with a substrate projection line of the fringe field, wherein retardation of the liquid crystal layer is $(2n+1)\lambda/4$ (here, λ is wave of light and n is a positive number).

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view showing a conventional reflective type FFS-LCD when electric field is off.

FIG. 2 is a perspective view showing a conventional reflective type FFS-LCD when a fringe field is applied.

FIG. 3 is a perspective view of a reflective type FFS-LCD according to a first embodiment of this invention.

FIG. 4 is a plan view of a lower substrate according to the first embodiment of this invention.

FIG. 5 is a drawing describing operation of a reflective type FFS-LCD according the first embodiment of this invention when the electric field is off.

FIG. 6 is a drawing describing the operation of a reflective type FFS-LCD according to a first embodiment of this invention.

FIG. 7 is a perspective view of a reflective type FFS-LCD according to a second embodiment of this invention.

FIG. 8 is a drawing describing operation of a reflective type FFS-LCD according to the second embodiment of this invention when the electric field is off.

FIG. 9 is a drawing describing operation of a reflective type FFS-LCD according to a second embodiment of this invention when a fringe field is applied.

FIG. 10 is a graph showing a reflectance in accordance with a retardation($d\Delta n$) in a reflective type FFS-LCD accordance with this invention.

FIG. 11 is a graph showing a contrast ratio according

to an azimuth in a reflective type FFS-LCD of this invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

A FIRST EMBODIMENT: A REFLECTIVE TYPE FFS-LCD OF NORMALLY WHITE TYPE

FIG. 3 is a perspective view of a reflective type FFS-LCD according to this invention. Referring to FIG. 3, a lower substrate 40 is opposed to an upper substrate 60 with a selected distance d_{11} (hereinafter, cell gap). A liquid crystal layer 65 including a plurality of liquid crystal molecules 65a, is interposed between the lower 40 substrate and the upper substrate 60. At this time, a liquid crystal molecule 65a of the liquid crystal layer 60 is nematic, and dielectric anisotropy may be positive or negative. In this embodiment, for example, material of positive dielectric anisotropy is used. And, retardation of the liquid crystal layer 65, i.e. the product of the cell gap d_{11} and the index of refraction anisotropy of the liquid crystal molecule 65a, is $(2n+1)\lambda/4$.

A counter electrode 43a and a pixel electrode 46a are disposed on the inside surface of the lower substrate 40 so as to form a fringe field to drive the liquid crystal molecule 65a. Here, the inside plane structure of the lower substrate 40 on which the counter electrode 43a and the pixel electrode 46 is formed, is presented in FIG. 4. Referring to FIG. 4, a plurality of gate bus lines 41a, 41b are extended and arranged to an x direction of a drawing with a selected interval on the lower substrate 40. And, a plurality of data bus lines 47a, 47b are also extended to a y direction of a drawing with a selected interval on the lower substrate 40, thereby defining a unit pixel with the gate bus lines 41a, 41b. In a drawing, only a pair of gate bus lines 41a, 41b and a pair of data bus lines 47a, 47b are illustrated. A gate insulating layer 44 is sandwiched between the gate bus lines 41a, 41b and the data bus lines

47a,47b thereby insulating themselves from each other. A common signal line 42 is extended to some direction, for example, to the x direction, and located between a pair of the gate bus lines 41a,41b. For example, it is desirable
 5 that the common signal line 42 is disposed in a location closer to the previous gate bus line 41b than gate bus line 41a selecting a pixel. Here, to shorten RC delay time, the gate bus lines 41a,41b, the common signal line 42 and the data bus lines 47a,47b are formed out of a metal layer or
 10 more than two alloy layers among groups which are composed of Al, Mo, Ti, W, Ta, Cr having relatively good conductive property and combinations thereof.

A counter electrode 43 is formed at each unit pixel of the lower electrode 43. Here, the counter electrode 43 is
 15 formed on the surface of the lower substrate 40 and formed so as to be contacted with the common signal line 42. The counter electrode 43 is contacted with the common signal line 42 and therefore applied of the common signal. At this time, the counter electrode 43 includes a plurality of
 20 branches 43a which are extended parallel with the data bus lines 47a,47b, and a body part 43b connecting groups of the branches 43a. At this time, the body part 43b is in part contacted with the common signal line 42. Here, the respective branches 43a have a selected width P11 and are
 25 spaced each other with a selected distance L11. The width P11 and the distance L11 of the branches 43b are decided by considering the width of a pixel electrode and the distance with a pixel electrode which will be formed later.

A pixel electrode 46 is also formed at each unit pixel
 30 of the lower substrate 40. At this time, the pixel electrode 46 is formed on a gate insulation layer 44 so as to be overlapped with the counter electrode 43. The pixel electrode 46 includes strips 46a which are respectively disposed between the branches 43a of the counter electrode
 35 43 and a bar 46b which is overlapped with the body part 43b of the counter electrode 43 connecting groups of the strips

46a. At this time, strips 46a have a selected width P12 and are spaced each other with a selected distance L12. And, the widths P12 of the strips 46a may be equal to or narrower than interval L11 of the branches 43a. The strips
 5 46b are located between the branches 43b of the counter electrode. Here, the strip 46a of the pixel electrode 46 and the branch 43a of the counter electrode 43 are separated by a selected distance. To form a fringe field, it is desirable that interval between the strip 46b of the
 10 pixel electrode 46 and the branch 43b of the counter electrode 43 is narrower than that of the cell gap d11, and for example, when the size of unit pixel is $110\mu\text{m} \times 330\mu\text{m}$, is formed to above $0.1\mu\text{m}$ to below $5\mu\text{m}$. And, the widths P11, P12 of those electrodes 43a, 46a should be formed such that the
 15 liquid crystal molecules in the upper portions of the electrodes 43a, 43b are sufficiently driven by the fringe field formed between electrodes 43a, 46a. In addition, the ratio of the width P12 of the strip 46a of the pixel electrode 46 to the width P11 of the branch 43a of the
 20 counter electrode 43 is 0.2 to 4 or so. Here, the width and distance of the branches 43a of the counter electrode 43 and the strips 46a of the pixel electrode are adjustable according to the size of unit pixel, and number of the same. However, the widths of the electrodes 43a, 46a should be
 25 formed such that the liquid crystal molecules in the upper of the electrodes 43a, 46a are sufficiently driven by the fringe field between the electrodes 43a, 46a.

A thin film transistor 50, a switching device, is formed near a crossing point of the gate bus lines 41a, 41b
 30 and the data bus lines 47a, 47b. The thin film transistor 50 switches the signal of the data bus line 47a to the pixel electrode 46 when selecting the gate bus line 41a.

A storage capacitor Cst occurs in the part which the counter electrode 43 and the pixel electrode 46 are
 35 overlapped, the part which the body part 43b of the counter electrode 43 and the bar 46b of the pixel electrode 46 are

overlapped. This storage capacitor Cst acts to maintain data signal during a frame.

Meanwhile, a color filter(not shown) is arranged on the inside surface of the upper substrate 60.

5 And, a first alignment layer 53 is formed on the resultant of the lower substrate 40, and a second alignment layer 63 is formed at an inner surface of the color filter on the upper substrate 60. The first and the second alignment layers 53,63 have the surfaces on which liquid
10 crystal molecule 65a is arranged to a selected direction. The first and the second alignment layers 53,63 are the homogeneous alignment layers which are treated so that the liquid crystal molecule has a pretilt angle of 0 to 10°, and have the rubbing axes R1,R2 respectively. Here, the
15 rubbing axis R1 of the first alignment layer 53 is at a selected angle(Ψ) with the direction of an x axis(hereinafter, projection line of a fringe field). At this time, the angle which the rubbing axis R1 of the first alignment layer 53 and the direction of the x
20 axis(hereinafter, projection line of a fringe field) form, is adjusted in the range of 10 to 85° according to the dielectric anisotropy so as to obtain the maximum transmissivity. The rubbing axis R2 of the second alignment layer 63 is anti-parallel to the rubbing axis R1 of the
25 first alignment layer 53, that is, rubbed so as to have the angle difference of about 180°.

And, a polarizer 70 is disposed on the outside surface of the upper substrate 60, and a polarizing axis 70a is disposed parallel to the rubbing axes R1,R2. A reflective
30 plate 75 is disposed on the out side of the lower substrate 40. At this time, the reflective plate 75 acts to reflect an incident light to 180°.

And, an optical component such as a $\lambda/4$ plate which has been added to conventional reflective type FFS-LCD, is not
35 added to the reflective type FFS-LCD of this invention. Instead, the liquid crystal layer 65 serves as $\lambda/4$ plate by

adjusting retardation of the liquid crystal layer 65.

The reflective FFS-LCD of this invention having this composition operates as following.

First, when the gate bus line 41a is not selected, the
5 signal of the data bus line 47a is not transmitted to the
pixel electrode 46b, therefore a fringe field between the
counter electrode 43 and the pixel electrode 46b is not
formed. Consequently, a long axis is parallel to the
rubbing axes R1,R2 so that the liquid crystal molecules 65a
10 within the liquid crystal layer 65 are arranged almost
parallel to a surface of a substrate. Then, a natural light
100a, as illustrated in FIG. 5, becomes an incident light
100b proceeding to an equal direction to the polarizing
axis 70a by the polarizer 70. The incident light 100b
15 passes through the liquid crystal layer 65 which is
arranged so that the rubbing axes R1,R2 and the long axis
of the liquid crystal molecule are equal, and the
proceeding direction thereof is not changed. The incident
light 100b which has passed through the liquid crystal
20 layer 65, is reflected by the reflective plate 75, thereby
becoming a reflected light 110a.

The reflected light 110a passes through the liquid
crystal layer 65 again and the proceeding direction thereof
is not changed. Consequently, the proceeding direction of
25 the reflected light 110a is equal to the polarizing axis
70a of the polarizer 70, thereby passing through the
polarizer 70. Accordingly, a screen is in a white state.

Meanwhile, when a scanning signal is transmitted to the
gate bus line 41a and a display signal is transmitted to
30 the data bus line 47a, a thin film transistor 50 which is
formed near a crossing point of the gate bus line 41a and
the data bus line 47a, is turned on and therefore
transmitted to the pixel electrode 46. At this time, a
common signal having a different voltage from the display
35 signal is continuously applied to the counter electrode 43,
and therefore a fringe field F is formed between the

counter electrode 43 and the pixel electrode 46 and on the upper of the electrode 43,46. Furthermore, when the fringe field F is projected to the lower substrate 40, the fringe field F and polarizing axis 70a make a selected angle.

5 Consequently, the liquid crystal molecule 65a is arranged so that the fringe field and the long axis or the optical axis thereof are parallel. Therefore, retardation occurs in the liquid crystal layer 65 by $(2n+1)\lambda/4$ (here, n is a positive number).

10 Then, a natural light 200a, as illustrated in FIG. 6, becomes an incident light 200b equal to the polarizing axis by passing through the polarizer 70. The incident light 200b which has passed through the polarizer 70 passes through the liquid crystal layer 65 having retardation of
15 $(2n+1)\lambda/4$, and therefore the proceeding direction thereof is changed, thereby becoming a right-circularly polarized incident light 200c. The right-circularly polarized incident light 200c is reflected by the reflective plate 75, thereby becoming a reflected light 210a being right-
20 circularly polarized.

The reflected light 210a becomes a reflected light 210b orthogonal to the polarizing axis 70a by retardation of the liquid crystal layer 65 again. Consequently, a screen is in a dark state. Therefore, a display can be realized by
25 normally white method without the $\lambda/4$ plate.

EMBODIMENT 2: REFLECTIVE TYPE FFS-LCD BY NORMALLY BLACK METHOD

30 FIG. 7 is a perspective view of a reflective type FFS-LCD according to a second embodiment of this invention. In this embodiment, a structure of the lower substrate 40, a structure of the upper substrate 60, the liquid crystal layer 65 and the reflective plate 75 are equal to those in
35 the first embodiment and only disposition of the polarizer 70 is different. A polarizing axis 70b of the polarizer 70

is at a selected angle, preferably 45° , with the rubbing axes R1,R2 so that a reflective FFS-LCD according to this embodiment, as illustrated in FIG. 7, is operated by a normally black method.

5 Operation of this reflective FFS-LCD by the normally black method is described.

First, before a fringe field is formed, long axes of the liquid crystal molecules 65a coincide with the rubbing axes R1,R2 and are arranged almost parallel to the
10 substrates. Then, a natural light 300a, as illustrated in FIG. 8, by the polarizer 70, becomes an incident light 300b proceeding to an equal direction to the polarizing axis 70a. The incident light 300b is at an angle of 45° with the long axis of the liquid crystal molecule, thereby becoming an
15 incident light 300c proceeding to an equal direction to the rubbing axes R1,R2, passing through the liquid crystal layer 65. The incident light 300c which has passed through the liquid crystal layer 65 is reflected by the reflective plate 75, thereby becoming a reflected light 310a.

20 The proceeding direction of the reflected light 310a is at an angle of 45° with the long axis of the liquid crystal molecule 65a, thereby becoming a reflected light 310b orthogonal to a polarizing axis 70b, passing through the liquid crystal layer 65. The proceeding direction of the
25 reflected light 310b which has passed through the liquid crystal layer 65 is perpendicular to the axis of the polarized light 70b, thereby not passing through the polarizer 70. Accordingly, a screen is in a dark state.

Meanwhile, when a fringe field F is formed, the liquid
30 crystal molecule 65a is arranged so that the fringe field F and the long axis or the short axis thereof are parallel, and therefore retardation occurs in the liquid crystal layer 65 by $(2n+1)\lambda/4$ (here, n is a positive number). A natural light 400a, as illustrated in FIG. 9, becomes an
35 incident light 400b equal to the polarizing axis 70b by passing through the polarizer 70. The incident light 200b

which has passed through the polarizer 70 is equal to the long axis of the liquid crystal molecule 65a which is twisted by the fringe field F, thereby passing through the liquid crystal layer 65 without changing its polarization state. An incident light 400c which has passed through the liquid crystal layer 65 is reflected by the reflective plate 75, thereby becoming a reflected light 410a.

The reflected light 410a is equal to the optical axis of the liquid crystal molecule 65 which is arranged in a fringe field form, thereby passing through the liquid crystal layer 65 without changing its polarization state. The proceeding direction of the reflected light 410a which has passed through the liquid crystal layer 65 is equal to the polarizing axis 70b, thereby passing through the polarizer 70. Accordingly, a screen is in a white state. Consequently, a display can be realized by the normally black method without using the $\lambda/4$ plate.

FIG. 10 of accompanying drawings is a graph showing reflectance in accordance with retardation ($d\Delta n$) in a reflective type FFS-LCD according to this invention. According to FIG. 8, when λ is 550nm, the points which reflectance are 0 and 0.9 show periodically. At this time, at the point of 0 retardation is $(2n+1)\lambda/4$ and at the point of 0.9 retardation is $2n/\lambda$. Consequently, when retardation of the liquid crystal layer 65 is $(2n+1)\lambda/4$, a display can be realized without the $\lambda/4$ plate.

FIG. 11 is a graph showing contrast ratio according to azimuth in a reflective type FFS-LCD of this invention. According to FIG. 11, when polar angle (θ) is more than 30° , contrast ratio is more than 10, and therefore good contrast ratio can be obtained without the $\lambda/4$ board.

This invention is not limited to the embodiments as described above.

For example, according to the embodiments of this invention, the pixel electrode and the counter electrode

are formed in the comb forms. However, being not limited to this, the pixel electrode and the counter electrode can be formed in any form so as to form a fringe field.

5 A reflective type FFS-LCD of this invention has effects as following.

First, in reflective type FFS-LCD, retardation($d\Delta n$) uses material having retardation of $(2n+1)\lambda/4$ as the liquid crystal layer. Consequently, the liquid crystal layer
10 serves as a conventional $\lambda/4$ plate, thereby not requiring to form an extra $\lambda/4$ plate. Accordingly, intensity of light increases and price decreases.

Moreover, the liquid crystal molecules between the counter electrode and the pixel electrode and on the upper
15 of the electrodes, are all operated by the fringe field, and therefore reflectance of a reflective type FFS-LCD is further improved.

Various other modifications will be apparent to those skilled in the art and can be easily carried out without
20 departing from the spirit and the scope of the present invention as defined by the accompanying claims.

WHAT IS CLAIMED IS:

1. A reflective type fringe field switching mode liquid crystal display("a reflective FFS-LCD") comprising:

5 a liquid crystal layer having a plurality of the liquid crystal molecules;

a first substrate disposed on one side of the liquid crystal layer and in which a counter electrode and a pixel electrode, both for generating a fringe field to drive the liquid crystal molecules are formed;

a second substrate disposed on the other side of the liquid crystal layer;

a first homogeneous alignment layer interposed between the liquid crystal layer and the first substrate and having a rubbing axis in a selected direction;

a second homogeneous alignment layer interposed between the liquid crystal layer and the second substrate, and having a rubbing axis in a selected direction;

a polarizer disposed on an out side of one of the first substrate and the second substrate, and having a selected polarizing axis; and

a reflective plate disposed on an out side of the other of the first substrate and the second substrate,

wherein retardation of the liquid crystal layer is $(2n+1)\lambda/4$ (here, λ is wave of light and n is a positive number).

2. The reflective type FFS-LCD according to claim 1, wherein a rubbing axis of the first homogeneous alignment layer and a rubbing axis of the second homogeneous alignment layer are anti-parallel each other.

3. The reflective type FFS-LCD according to claim 2, wherein the rubbing axes of the first and the second alignment layers are at an angle of 10 to 85° with a substrate projection line of the fringe field.

4. The reflective type FFS-LCD according to claim 1,
wherein the rubbing axes of the first and the second
alignment layers and a polarizing axis of the polarizer
5 coincide.

5. The reflective type FFS-LCD according to claim 1,
wherein the rubbing axes of the first and the second
alignment layers and the polarizing axis of the polarizer
10 are at an angle of 20 to 60°.

6. The reflective type FFS-LCD according to claim 5,
wherein the rubbing axes of the first and the second
alignment layers and the polarization axis of the polarizer
15 are at an angle of 45°.

7. A reflective FFS-LCD comprising:

a liquid crystal layer having a plurality of liquid
crystal molecules;

20 a first substrate disposed on one side of the liquid
crystal layer and on which a counter electrode and a pixel
electrode, both for generating a fringe field to drive the
liquid crystal molecules are formed;

a second substrate disposed on the other side of the
25 liquid crystal layer;

a first homogeneous alignment layer interposed between
the liquid crystal layer and the first substrate and having
a rubbing axis in a selected direction;

a second homogeneous alignment layer interposed between
30 the liquid crystal layer and the second substrate and
having a rubbing axis in a selected direction anti-parallel
to the rubbing axis of the first homogeneous alignment
layer;

a polarizer disposed on an out side of one of the first
35 substrate and the second substrate, and having a selected
polarizing axis; and

a reflective plate disposed on an out side of the other substrate of the first substrate and the second substrate,

wherein the rubbing axes of the first and the second alignment layers are at an angle of 10 to 85° with a substrate projection line of the fringe field,

wherein retardation of the liquid crystal layer is $(2n+1)\lambda/4$ (here, λ is wave of light and n is a positive number).

10 8. The reflective type FFS-LCD according to claim 1, wherein the rubbing axes of the first and the second alignment layers and the polarizing axis of the polarizer coincide.

15 9. The reflective type FFS-LCD according to claim 1, wherein the rubbing axes of the first and the second alignment layers and the polarizing axis of the polarizer are at an angle of 20 to 60°.

20 10. The reflective type FFS-LCD according to claim 5, wherein the rubbing axes of the first and the second alignment layers and the polarizing axis of the polarizer are at an angle of 45°.

006290"47040950

ABSTRACT OF DISCLOSURE

00507014 062900

This invention disclose a reflective type FFS-LCD. A reflective type FFS-LCD of this initiated invention includes: a liquid crystal layer having a plurality of the liquid crystal molecules; a first substrate disposed on one side of the liquid crystal layer and in which a counter electrode and a pixel electrode, both for generating a fringe field to drive the liquid crystal molecules are formed; a second substrate disposed on the other side of the liquid crystal layer; a first homogeneous alignment layer interposed between the liquid crystal layer and the first substrate and having a rubbing axis in a selected direction; a second homogeneous alignment layer interposed between the liquid crystal layer and the second substrate, and having a rubbing axis in a selected direction; a polarizer disposed on an out side of one of the first substrate and the second substrate, and having a selected polarizing axis; and a reflective plate disposed on an out side of the other of the first substrate and the second substrate, wherein retardation of the liquid crystal layer is $(2n+1)\lambda/4$ (here, λ is wave of light and n is a positive number).

FIG.1
(PRIOR ART)




FIG.2




FIG.3




FIG.4




FIG.5




FIG.6




FIG.7





FIG.8




FIG.9




FIG.10










FIG.11

Contrast ratio	
	30.000
	20.000
	10.000
	5.000



Docket:

COMBINED DECLARATION AND POWER OF ATTORNEY

(ORIGINAL, DESIGN, NATIONAL STAGE OF PCT, SUPPLEMENTAL, DIVISIONAL,
CONTINUATION OR CIP)

As a below named inventor, I hereby declare that:

TYPE OF DECLARATION

This declaration is of the following type: (check one applicable item below)

- ☒ original
☐ design
☐ supplemental

Note: If the Declaration is for an International Application being filed as a divisional, continuation or continuation-in-part application, do not check next item; check appropriate one of last three items.

- ☐ national stage of PCT

Note: If one of the following 3 items apply, then complete and also attach ADDED PAGES FOR DIVISIONAL, CONTINUATION OR CIP.

- ☐ divisional
☐ continuation
☐ continuation-in-part (CIP)

INVENTORSHIP IDENTIFICATION

WARNING: If the inventors are each not the inventors of all the claims, an explanation of the facts, including the ownership of all the claims at the time the last claimed invention was made, should be submitted.

My residence, post office address and citizenship are as stated below, next to my name. I believe that I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter that is claimed, and for which a patent is sought on the invention entitled:

TITLE OF INVENTION

REFLECTIVE TYPE-FRINGE FIELD SWITCHING MODE LCD

SPECIFICATION IDENTIFICATION

the specification of which: (complete (a), (b) or (c))

- ☒ (a) is attached hereto.
☐ (b) was filed on _____ as ☐ Serial No. _____ or ☐ Express Mail No. (as Serial No. not yet known) _____ and was amended on _____ (if applicable).

Note: Amendments filed after the original papers are deposited with the PTO that contain new matter are not accorded a filing date by being referred to in the Declaration. Accordingly, the amendments involved are those filed with the application papers or, in the case of a supplemental Declaration, are those amendments claiming matter not encompassed in the original statement of invention or claims. See 37 CFR 1.67.

- ☐ (c) was described and claimed in PCT International Application No. _____ filed on _____ and as amended under PCT Article 19 on _____ (if any).

ACKNOWLEDGEMENT OF REVIEW OF PAPERS AND DUTY OF CANDOR

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information, which is material to patentability as defined in 37, Code of Federal Regulations, § 1.56,

(also check the following items, if desired)

- ☐ and which is material to the examination of this application, namely, information where there is a substantial likelihood that a reasonable Examiner would consider it important in deciding whether to allow the application to issue as a patent, and
- ☐ in compliance with this duty, there is attached an information disclosure statement, in accordance with 37 CFR 1.98.

PRIORITY CLAIM (35 U.S.C. § 119(a)-(d))

I hereby claim foreign priority benefits under Title 35, United States Code, § 119(a)-(d) of any foreign application(s) for patent or inventor's certificate or of any PCT international application(s) designating at least one country other than the United States of America listed below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed.

(complete (d) or (e))

- ☐ (d) no such applications have been filed.
- ☒ (e) such applications have been filed as follows.

Note: Where item (c) is entered above and the international application which designated the U.S. itself claimed priority check item (e), enter the details below and make the priority claim.

PRIOR FOREIGN/PCT APPLICATION(S) FILED WITHIN 12 MONTHS (6 MONTHS FOR DESIGN) PRIOR TO THIS APPLICATION AND ANY PRIORITY CLAIMS UNDER 35 U.S.C. § 119(a)-(d)

COUNTRY (OR INDICATE IF PCT)	APPLICATION NUMBER	DATE OF FILING (day/month/year)	PRIORITY CLAIMED UNDER 35 USC 119
Republic of Korea	99-25214	29/06/1999	<input checked="" type="checkbox"/> YES NO <input type="checkbox"/>
			<input type="checkbox"/> YES NO <input type="checkbox"/>
			<input type="checkbox"/> YES NO <input type="checkbox"/>
			<input type="checkbox"/> YES NO <input type="checkbox"/>
			<input type="checkbox"/> YES NO <input type="checkbox"/>

CLAIM FOR BENEFIT OF PRIOR U.S. PROVISIONAL APPLICATION(S)
(34 U.S.C. § 119(e))

I hereby claim the benefit under Title 35, United States Code, § 119(e) of any United States provisional application(s) listed below:

PROVISIONAL APPLICATION NUMBER	FILING DATE

ALL FOREIGN APPLICATION(S), IF ANY, FILED MORE THAN 12 MONTHS
(6 MONTHS FOR DESIGN) PRIOR TO THIS U.S. APPLICATION

Note: If the application filed more than 12 months from the filing date of this application is a PCT filing forming the basis for this application entering the United States as (1) the national stage or (2) a continuation, divisional, or continuation-in-part, then also complete ADDED PAGES TO COMBINED DECLARATION AND POWER OF ATTORNEY FOR DIVISIONAL, CONTINUATION OR CIP APPLICATION for benefit of the prior U.S. or PCT application(s) under 35 U.S.C. § 120.

POWER OF ATTORNEY

I hereby appoint the following practitioner(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith *(list name and registration number)*.

Thomas F. Peterson, 24790; Richard J. Streit, 25765; Timothy J. Keefer, 35567; Dennis K. Scheer, 39356; Douglas S. Rupert, 44434; Steven L. Schmid, 39358; Paul B. West, 18947; Joseph H. Handelman, 26179; Peter D. Galloway 27885; John Richards, 31503; Iain C. Baillie, 24090; Richard P. Berg, 28145

☐ Attached, as part of this declaration and power of attorney, is the authorization of the above-named practitioner(s) to accept and follow instructions from my representative(s).

SEND CORRESPONDENCE TO:

Thomas F. Peterson
c/o Ladas & Parry
224 South Michigan Avenue
Chicago, Illinois 60604

DIRECT TELEPHONE CALLS TO:
(Name and telephone number)

(312) 427-1300

DECLARATION

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

006290" 41020960

SIGNATURE(S)

Note: Carefully indicate the family (or last) name, as it should appear on the filing receipt and all other documents.

Full name of sole or first inventor

Seung Ho _____ Hong _____
(Given Name) (Middle Initial or Name) (Family (or Last) Name)

Inventor's signature _____

Date June 23, 2000 **Country of Citizenship** Republic of Korea

Residence Kyoungki-do

Post Office Address 1142-1106, Samsung Jangmi Apt., 1092, Sanpon-dong,
Kunpo, Kyoungki-do, Korea

Full name of second joint inventor, if any

Seung Hee _____ Lee _____
(Given Name) (Middle Initial or Name) (Family (or Last) Name)

Inventor's signature _____

Date June 23, 2000 **Country of Citizenship** Republic of Korea

Residence Kyoungki-do

Post Office Address 102-1206, Hyundai Apt., 49-1, Changjeon-dong, Ich'on,
Kyoungki-do, Korea

Full name of third joint inventor, if any

(Given Name) (Middle Initial or Name) (Family (or Last) Name)

Inventor's signature _____

Date _____ **Country of Citizenship** _____

Residence _____

Post Office Address _____